



NO.	CONTENTS	SUPER TURBO		D1	
		2 WD	4 WD	2 WD	4 WD
1	Year of the car is open	✓			
2	Car's weight include that of driver	1,350 kg.	1,400 kg.	1,250 kg.	1,300 kg.
		1,300 kg.	1,350 kg.	1,200 kg.	1,250 kg.
3	Weight for car must be in block shape with lid and it must be fixed firmly with car's body by using bolts and nuts beside of driver's seat	✓			
4	Car's body and engine do not have to be that of the same brand.	✓			
5	Car's shape must be remained as can tell by looking which brand and model it is	✓			
6	Cockpit floor must be that of standard. Cutting off is not allowed.	✓			
7	Engine	Turbo installed Not Over 3250 cc. 3050 cc.		Turbo installed Not Over 2250 cc.	
		3 rotor Turbo installed		2 rotor Turbo installed	
		N/A Engine Not Over 5050 cc.		N/A Engine Not Over 3850 cc.	
8	The car is allowed to install only 1 turbo with air restrictor. The narrowest part must not exceed 10 cm. measured from the the tip of compressor wheel. (ROTARY engine)	43 mm.		38 mm.	
		47 mm.		42 mm.	
9	The material of engine block and cylinder head cover must be as factory standard. Holding points must be remained in both benzine and diesel engine.	✓			
10	DRY SUMP system	✓			
11	Any gas or liquid substance that means to mix with air in air intake tube as to reduce temperature is not allowed. Only Intercooler Air-To-Air type is allowed	✓			
12	Water Inter Cooler is allowed but water pump and any other external spray as to reduce the heat of inter cooler is not allowed	✓			
13	Transmission	Manual Transmission			
		Automatic Paddle Shift			
		Sequential Paddle Shift			
14	Suspension's holding point can be moved from the original point not more than 20 mm. in radius.	✓			
15	Shock absorber position and its working system must be remained the same as factory setting	✓			
16	Suspension system parts must be remained standard as factory setting,	✗			
17	Aero part can be freely installed as it is not harmful to other	✓			
18	Tail pipe must point out at the back of the car only.	✗			
19	Fuel tank are free. If installed in the cabin, it must be completely surrounded by a fireproof and shockproof structure.	✓			
20	Allowed to add no more than 5 liters to tank A.	✓			
21	Tyres that allowed to used in the race (Provided from organizer only)			245/625-17 260/650-18	
22	For rain tires, use only Giti brand tires, model GTR1 (WET).	✓			
23	Rear camera must be installed and there must be at least 5" monitor installed inside cockpit in middle console.	✓			
24	Must install Apps STT RACE CONTROL	✓			
25	Safety system (Roll,Racing Seat, at least 5 anchors BELT,Electric Breaker,Fire Extinguisher) and window net at driver side.	✓			