



NO.	CONTENTS	D 3
1	Year of the car is open	✓
2	Car's weight include that of driver.	TURBO ENGINE 1,110 kg.
		NA. ENGINE 1,080 kg
3	Weight for car must be in block shape with lid and it must be fixed firmly with car's body by using bolts and nuts beside of driver's seat.	✓
4	Car's body and engine do not have to be that of the same brand.	✓
5	Car's shape must be remained as can tell by looking which brand and model it is.	✓
6	Cockpit floor must be that of standard. Cutting off is not allowed.	✓
7	Engine	N/A Not More Than 1850 cc.
		Turbo installed Not More Than 1550 cc.
8	For N/A engine, there must be only 1 working throttle. The narrowest part must not exceed 10 cm. Measured from the tip of compressor wheel.	60 mm.
9	The car is allowed to install only 1 turbo with air restrictor. The narrowest part must not exceed 10 cm. Measured from the tip of compressor wheel. And the compressor ambient air inlet must have only one hold.	<b>Gasoline engine</b> 30 mm.
		<b>Diesel engine</b> 35 mm.
10	The material of engine block and cylinder head cover must be as factory standard. Holding points must be remained in both gasoline engine and diesel engine.	✓
11	DRY SUMP system.	✗
12	Any gas or liquid substance that means to mix with air in air intake tube as to reduce temperature is not allowed. Only intercooler Air-To-Air type is allowed.	✓
13	Water intercooler is allowed but water pump and any other external spray as to reduce the heat of intercooler is not allowed.	✓
14	Transmission	Manual Transmission
		Sequential + Gear lever + 20 kg.
		Sequential + Paddle Shift + 30 kg.
15	The suspension mounting points must be the original mounting points of the vehicle model. Do not change, modify, or edit.	✓
16	The suspension rubber bushing material can be changed to a Ball Joint.	✓
17	Caliper and carbon fiber disc system.	✗
18	Shock absorber position and its working system must be remained the same as factory setting.	✓
19	Suspension system parts must be remained standard as factory setting.	✓
20	Aero part can be freely installed as it is not harmful to other.	✓
21	Tail pipe must point out at the back of the car only.	✓
22	Rim and center lock system.	✗
23	Fuel tank are free. If installed in the cabin, it must be completely surrounded by a fireproof and shockproof structure.	✓
24	Allowed to add no more than 5 liters to tank A.	✓
25	Tyres that allowed to used in the race (Provided from organizer only).	  <span style="margin-left: 10px;">195/55-15</span>
26	Rear camera must be installed and there must be at least 5" monitor installed inside cockpit in middle console.	✓
27	Must install Apps STT RACE CONTROL	✓
28	Safety system (Roll bar, Racing seat, at least 8 anchors BELT, Electric breaker, Fire extinguisher) and window net at driver side.	✓